CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original Survey was by Frank W. Campbell under G.L.O. Contract No. 507, dated June 28, 1884.

Set a fir post 3 ft. long, 3 inches square, 24 inches in ground for 1/4 sec. corner marked 1/4 S on W face.

From which: A fir 30 inches in dia. bears $N40^{O}W$, 37 lks. dist. marked 1/4 S BT.

A fir 30 inches in dia. bears S40°E, 17 lks. dist. marked 1/4 S BT.

Index File No. L-13 DIAGRAM T4N R40E 1/4 S16 S15

Description of corner evidence found:

Found old white fir snag with visible scribe 1/4. Painted red . No evidence of the original corner post or the other BT could be found. The blaze is on the southeast side of tree making this the northwest BT.

Description of monument and accessories Lestablished to perpetuate the original location of this corner:

At record bearing and distance from the found Bearing Tree set a $2\frac{1}{2}$ " x 30" galvanized pipe with brass cap marked: Set pipe 26" deep with mound of stone to cap.

From which:

T4N R40E WM 1/4 S 16 S15 1978 OR PLS 1051

39-83

File No.

A fir 17" in dia. bears S77 $^{\rm O}$ E, 33.7 ft., scribed 1/4 S15 BT. A fir 12" in dia. bears N85 $^{\rm O}$ W, 49.6 ft., scribed 1/4 S16 BT.

Painted blazes red and 6" red band around both BT's. Placed 54-4's and 54-3's on old BT and both new BT's. Placed brass washer stamped PLS 1051 on foot blazes of both BT's. Placed 54-2 and 54-4 sign on metal fence post 5' south of corner. Placed 54-5 sign on tree on east side of forest service road No. N53 200 feet West of corner.

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1 0 5 1

I hereby certify that the above corner monument was re-established as herein described.

Witnesses: Rodger Orton

Glen Wagoner Jeff Anderson

June 20, 1978

State of Oregon the County Surveyor	t the within instrument was filed in i	this office
for record on the	, 19 /8	UNION COUNTY SURVEYOR
6-7100-57 (9/71)		Date Received
		Date Filed

Form F