

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-15

History of original corner establishment:

Deputy F.W. Campbell in 1884 under Contract No. 507  
Set a Fir post  
Marked: 28" fir N60E 10 lks  
18" fir S53W 15 lks.

DIABAN  
T4N R40E  
1/4 815  
822

Description of corner evidence found:

1" Iron pipe with a 2 1/2" brass cap

Stamped:

T4N R40E  
1/4 815  
822  
ORLS 506  
1973

Orig. 28" now 36" D-Fir snag N54E (record N60E) 6.6'  
to face-scribing visible on upper blaze

Orig. 18" now 20" Wh. Fir snag S53W 9.9' to face  
scribing visible on upper blaze

Description of monument and accessories | established to perpetuate the  
original location of this corner:

Marked: 9" Wh. Fir N86W 46.5' scribed 1/4S15BT

15" " " N4E 73.5' " "

22" " " N78E 70.9' " "

Drove 5/8" Iron rod in center of 20" Wh. Fir Stump with a red plastic  
cap marked PLS 896 S12-33E 61.05'

UNION COUNTY  
SURVEYOR  
Date Received 1-21-92  
Date Filed 1-22-92  
By [Signature]  
File No. 009-1992 R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

[Signature]  
OREGON  
JULY 11, 1980  
LARRY D. BISHOP  
008

Office of..... County of.....

State of..... I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by .....

(COUNTY OFFICIAL)

(DEPUTY)

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

N-15

**History of original corner establishment:**


Corner established in 1884 by Frank W. Campbell, under General Land Office Contract No. 507.

**Surveyor General Records states:**

Set a fir post 3 feet long 3" square 24" in ground for 1/4 section corner marked 1/4 S on N. face

from which:

- A fir 28" diam. bears N.60°E 10 links distance marked 1/4 S BT
- A fir 18" diam. bears S.53°W. 15 links distance markde 1/4 S BT



**Description of corner evidence found:**

At assumed corner the post was not in evidence. I found the original bearing trees:

- A fir, live and sound, now 35" diam. in the NE Quadrant
- A fir, live and sound, now 27" diam. in the S.W. Quadrant.


**Description of monument and accessories I established to perpetuate the**

original location of this corner As the evidence found agrees with the original GLO notes, I reversed the bearings and distances from the BTs found and set a 1" galvanized iron pipe 36" long with a 2 1/2" Brass Cap marked

From which (Original BTS):

- A fir (now 35" diam) bears N.60°E 6.6 feet dist. marked 1/4 S BT
- A fir (now 27" diam) bears S,53°W 9.9 feet dist.

No new BTs were needed.



**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Ralph P. Thompson*

OREGON  
MAY 13, 1960  
RALPH P. THOMPSON  
508

<b>UNION COUNTY SURVEYOR</b>	
Date Received	_____
Date Filed	_____
By	_____
File No.	45-83 R

Office of...county...surveyor..... County of.....Union.....  
 State of.....Oregon....., I hereby certify that the within instrument was filed in this office  
 for record on the 27 day of June....., 1973, at 9 o'clock A.m., (signed)  
*Ralph P. Thompson* by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)