## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

|   | N-17                  |
|---|-----------------------|
| History of original corner establishment:   | DIAGRAM               |
| Corner established in 1885 by Frank W. Campbell, under Gener Land Office Contract No. 507 | T4N R4O E             |
| Surveyor General Records states:  | S.15   S.14           |
| Set a Basalt Stone 10x8x8 inches 7" in ground f   | on —                  |
| corner to Sections 14-15-22 &23 marked with 3 note  | sheps S.22 S.23       |
| on S. and 2 notches on E. edges From which:   | 1                     |
| A fir 8" diam. bears N.79 E. 272 links dist.  |                       |
| Marked T4N R4OE S.14 BT   |                       |
| A fir 10" diam. bears S.17°E. 150 links dist.   |                       |
| Marked T4N R4OE S.23 BT   |                       |
| A fir 12" diam. bears S.61°W. 140 links dist.<br>Marked T4N R40E S.22 BT                  |                       |
| A pine 30" diam. bears N.19°W. 93 links dist. N   | lawbed TAN RACE S 15  |
| Description of corner evidence found:   | Bጥ                    |
| At assumed location I found a 10x8x8 inch basalt s  | tone marked with      |
| 3 notches on S. and 2 notches on E. faces. from which:                                    |                       |
| A pine, live and sound, now 36" diam. bears N.1   | Our 07 34 1 / 63 70   |
| dist.   | 9 W. 95 links (61.38) |
|   |                       |
|   |                       |
|   |                       |
|   |                       |
|   |                       |
|   |                       |
|   |                       |
|   |                       |
| Description of monument and accessories I established to perpetuate the                   |                       |
| original location of this corner As the evidence found agrees wit                         | h the original notes  |
| I replaced the stone with a 1" galvanized iron pip  | e with a 2½"Brass     |
| Cap, and buried the stone alongside the new monume from which (new BTS)                   | nt, the B.C. marked:  |
| A fir, 10" diam. bears N.14°E. 113.0 feet dist.   |                       |
| marked T4n R40E S.14 BT   | T4N R4OE              |
| A pine, 11" diam. bears S.17°E. 48.7 feet dist.   | S.15   S.14           |
| marked T4N R40E S.23 BT<br>A pine, 10" diam. bears S.72°W. 17.6 feet dist.                |                       |
| marked T4N R40E S.22 BT   | S.22 S.23             |
|   | ORLS 506              |
| Note: I placed USFS bearing tree signs on the new   | 1973                  |
| BTs and a brass washer stamped ORLS 506 on th   | e lower blazes.       |
|   | UNION COUNTY          |
| REGISTERED  | SURVEYOR              |
| PROFESSIONAL  |                       |
| LAND BORVETON   | Date Received         |
| all all   |                       |
| Light hompson   | Date Filed            |
| OREGON<br>MAY 13, 1960  | l Rv                  |
| RALPH P. THOMPSON 508   | Ву                    |
| Office of county surveyor County of Union   | File No. 46-83 R      |
| State of Oregon , I hereby certify that the within instrument was file                    | d in this office      |
| for record on the   | A m. (signed)         |
| amel I rel  | witness / m. Annam.   |