

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-19


History of original corner establishment:

Corner was established by Frank W. Campbell under contract No. 507, dated June 28, 1884.

Set a basalt stone 10 x 9 x 8 inches, 7 ins. in the ground for ¼ sec. cor., mkd. ¼ on N face from which:

A fir 24" diam. bears S 13° E, 56 lks. dist. mkd. ¼ S BT.

A fir 24" diam. bears N 30° E, 63 lks. dist., mkd. ¼ S BT.



Description of corner evidence found:

Found 41" down (sawed) white fir with healed blaze, which was sawed out and full scribing found.

Stone not found.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½-inch brass cap on 2-inch iron pipe, 31 inches long, 6 inches out of ground in earth and rock mound with 6 ft. steel fence post set alongside with sign 54-4 attached.

12 inch fir bears S 25° W, 9.8 ft. dist., mkd. ¼ S 23 BT.

16 inch tamarack bears N 63° E, 40.9 ft. dist., mkd. ¼ S 14 BT.

Monument is marked: T 4 N R 40 E

¼ S 14
S 23

RPE 2808
1975



Office of.....Surveyor..... County of Union
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 26 day of August, 1976.
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 47-83 R
CRD 706-333