


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. P-21

History of original corner establishment:

Corner was originally established under G. L. O. contract No. 507 by Frank W. Campbell on August 10, 1884. Surveyor General's notes state: "Set a basalt stone 12x8x8 ins. 9 ins. in the ground for 1/4 Sec corner marked 1/4 on W. face from which a fir 12 ins. in diam bears N70°W., 29 lks. dist marked 1/4S BT. A fir 8 ins. diam. bears S70°E., 29 lks dist marked 1/4S BT."



Description of corner evidence found:

Found no trace of corner stone or BTs.

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" x 30" galvanized pipe and brass cap marked: Set pipe 24" in the ground and mound of stone around to cap.
From which by magnetic declination of N20°E:
A 20" Fir bears S72°E., 26.1 ft. scribed 1/4 S24 BT.
A 14" Fir bears S88°W., 18.1 ft. scribed 1/4 S23 BT.
Painted blazes red and 6" red band around.
Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BTs.
Placed 54-4 on steel fence post 5' south of the corner.

T4N R40E
 1/4
 |
S23 + S24
OR PLS 1051
 1981

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Beverly Weaselhead

June 16, 1981

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County Surveyor..... County of.....Union.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 24 day of.....August....., 1981
HOWARD L. PERRY by Mary J. Langley
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 8-27-81

Date Filed _____

By _____

File No. 55-83 R