


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Q-17

History of original corner establishment:

None.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" x 30" galvanized pipe and brass cap marked; Set pipe 24" in the ground. No rock in the area.

From which by magnetic declination of N20°E:

A 24" Lodgepole Pine bears N58°E., 39.6 ft., scribed S1/16 S23 BT.

A 26" Spruce bears N70°W., 67.7 ft., scribed S1/16 S22 BT.

Painted blazes red and 6" red band around.

Placed 54-3 and brass washer stamped PLS 1051 on BT.

Placed 54-9 on steel fence post 5' south of the corner.

T4N R40E
S1/16

S22 + S23

OR PLS 1051
1981

I hereby certify that the above corner monument was established as herein described.

Witnesses: Daniel Rowland
Beverly Weaselhead

June 15, 1981

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour
**OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051**

Office of... County Surveyor..... County of... Union.....

State of... Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 24 day of August, 1981.

HOWARD L. PERRY
(COUNTY OFFICIAL)

by Gary J. Knight
(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 98-276

Date Filed _____

By _____

File No. 56-83 R