Index File No. # 25

History	of	oria	inal	corner	estab	lishme	nt:
11131017	01	viiy	11100	COLLING	99190	3	,,,,,

Corner established by Frank W. Campbell under G.L.O. Corner established by Frank W. Campbell under G.L.O.
Contract #507 in August, 1884. Surveyor's General's
notes state: "Set a post 4 ft. long 4 ins. sqr.
24 ins. in ground for cor. to Sec. 24.25.19 & 30
marked: T.4.N.S19 on N.E., R.40 E.S.30 on S.E.,
R.39 E.S.25 on S.W. & S.24 on N.W. faces with 4
notches on N. & 2 on S. edges from which:
A Spruce 30 ins. dia. brs. N40 W341ks. dist. marked
T.4N.R.39E. S.24 B.T.. A Spruce 30ins. dia. brs. N30 S.351ks.
dist. marked T.4 N.R.40E. S.19 B.T.. A Spruce 26 ins. dia. brs.
S.19 E.381ks dist. marked T.4N.R.40E. S.30BT.. A Fir 10 ins.
dia. brs. S.69 W.471ks. dist. marked T.4N.R.39E. S.25B.T.."

DIAGRAM T4N R39E R40E **S19** S30

Description of corner evidence found:

No evidence of original corner could be found. No evidence of original corner could be found. A dilligent search was made before the survey and after the corner position was determined.

Corner falls in a small opening at foot of West slope and about 600' West of new logging road.

Description of monument and accessories I established to perpetuate the original location of this corner:

At single proportionate measurement from found corners, set $2\frac{1}{2}$ " x 30" galvanized pipe with brass cap marked: Set pipe 24" in the ground. R39E R40E S24 | S19 S25 | S30

T4N

No rock in the area.

OR PLS 1051 1978

29-83 R

File No.

From which: A Fir 20" in dia. bears N70°E 50.1 feet, scribed T4NR40ES19BT. A Fir 28" in dia. bears S30°E, 42.4 feet, scribed T4NR40ES30BT. A Fir 30" in dia. bears S86°W, 46.9 feet, scribed T4NR39ES25BT. A Fir 20" in dia. bears N04°W, 48.3 feet, scribed T4NR39ES24BT. Painted blazes red and 6" red band around. Placed 54-3s and 54-4s on BTs. Placed brass washer stamped PLS 1051 on foot blazes. Placed 54-4 on steel fence post 4' North of corner. Placed 54-5 on tree 35' East and on road 600' East of corner.

REGISTERED **PROFESSIONAL** AND SURVEYOR

OREGON U OCT. 17, 1975 BARRY B. BAI

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses:

David L. Landers Dan T. Rowland

October 26, 1978

Office of County Surveyor County	nty of Union	
State ofOregon I hereby certify that the for record on the 20 day of NO. yember	UNION COUNTY SURVEYOR	
by	JORVETOR	
(COUNTY OFFICIAL)	(DEPUTY)	
Form R6-7100-57 (9/71)	Date Received	
		Date filed