

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-19


History of original corner establishment:

Corner was established by Frank W. Campbell under G. L. O. contract No. 507, dated June 28, 1884.

Set a fir post, 3 ft. long, 3 ins. square, 24 ins. in the ground for ¼ sec. cor. mkd. ¼ S on N face, from which:

A spruce, 27 ins. diam. bears S 18° W, 19 lks. dist., mkd. ¼ S BT.

A spruce, 26 ins. diam. bears N 32° W, 20 lks dist., mkd. ¼ S BT.



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

Set a 2½-inch brass cap on 2-inch iron pipe, 31 inches long, 6 inches above the ground with a 6 ft. steel fence post alongside with sign 54-4 attached.

A 8-inch larch bears N 14° R, 4.0 ft. dist., mkd. ¼ S 23 BT.

A 7-inch fir bears S 22° E, 3.0 ft. dist., mkd. ¼ S 26 BT.

Monument marked:

T 4 N R 40 E

¼ S 23

S 26

RPE 2808

1976



Office of.....Surveyor..... County of.....Union.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office for record on the 26 day of August, 1976.

..... by

(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By 70-83R _____

File No. 690-700-000 _____