


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. S-10

History of original corner establishment:

Corner was set in 1977 by P.L.S. 645 based on different corner position then that established in 1976 by survey.




Description of corner evidence found:

Found 2 1/2" x 30" galvanized pipe set 25" in the ground, marked: "NW1/16S28" Two trees were blazed and scribed as bearing trees.

Corner is about 50' East of track road and near SW corner of timbered area.

Description of monument and accessories established to perpetuate the original location of this corner:

At surveyed point, which is N84°36'E, 2.31 feet from 1977 brass cap, set 2 1/2" x 30" galvanized pipe with brass cap marked: Set pipe 24" in the ground.



No rocks in the area.

From which 1977 bearing trees: A Fir 10" in dia. bears N13°E, 48.7 feet, scribed NWC1/16S28XBT. A Tamarac 10" in dia. bears S72°E, 50.0 feet scribed NWC1/16S28XBT. Placed 54-3s for my monument and 54-4s on BTs. Placed brass washer stamped PLS 1051 on foot blazes. Blazes are painted red, with yellow outside. Placed 54-2 and 54-4 on steel fence post 5' East and 54-2 and 54-9 on steel fence post 4' North of corner. Location tag on tree near corner.

**REGISTERED PROFESSIONAL LAND SURVEYOR**

*Barry B. Barbour*

OREGON  
OCT. 17, 1975  
BARRY B. BARBOUR  
1051

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers  
Dan T. Rowland

October 20, 1978

Office of.....County..Surveyor..... County of.....Union.....  
State of.....Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the...20... day of...November....., 1978.

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

**UNION COUNTY SURVEYOR**

---

Date Received 10-20-78

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 74-83R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history of this corner.

S-10

DIAGRAM  
Cap Stamped:  
NW-C-1/16  
S 28  
1977  
ORLS 645

Description of corner evidence found:

No evidence found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a stamped 2 1/2" brass cap on a 30" galv. iron pipe buried in a mound of stone.

I set two bearing trees as follows:

A spruce 8" dia., which bears N 16 E, 49.0 feet, scribed NW-C-1/16 S 28 BT.

A larch 10" dia., which bears S 63 E, 51.9 feet, scribed NW-C-1/16 S 28 BT.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James H. Hambleton*

12-20-77  
OREGON  
JULY 12, 1964  
JAMES H. HAMBLETON  
645

Office of..... County of.....

State of..... I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19....

..... by.....

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY  
SURVEYOR

Date Received \_\_\_\_\_

☆ GPO - 798-276

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 82-83R