


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. S-18

History of original corner establishment:

None.



Description of corner evidence found:

None .

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" x 30" galvanized pipe and brass cap marked; Set pipe 25" in the ground. No rock in the area.

From which by magnetic declination of N20°E;


A 12" Tamarac bears N82°E., 18.8 ft. scribed NWL/16S26 BT.

A 12" Tamarac bears S36°W., 19.0 ft. scribed NWL/16S26 BT.

Painted blazes red and 6" red band around.

Placed 54-3s, 54-9s and brass washers stamped PLS 1051 on BTs.

Placed 54-2 and 54-9 on steel fence post 5' east and 54-2 on steel fence post 5' north of the corner.



I hereby certify that the above corner monument was established as herein described.

Witnesses: Daniel Rowland  
Beverly Weasealhead

June 17, 1981

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Barry B. Barbour*

**OREGON  
OCT. 17, 1975  
BARRY B. BARBOUR  
1981**

Office of.....County..Surveyor..... County of....Union.....

State of.....Oregon..... I hereby certify that the within instrument was filed in this office

for record on the 24 day of.....August....., 1981

HOWARD L. PERRY by Barry B. Barbour

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received 7-28-81

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 77-83R