


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. T-12

History of original corner establishment:

Not set.



Description of corner evidence found:

Painted line trees near the surveyed point.

Corner falls near the Northeast corner of timbered area.

Description of monument and accessories established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" x 30" galvanized pipe with brass cap marked: Set pipe 25" in the ground.

T4N R40E
E1/16C — CS28
OR PLS 1051
1978

No rock in the area.

From which: A Tamarac 10" in dia. bears N30°E, 64.9 feet, scribed EC 1/16S28BT. A Tamarac 10" in dia. bears S21°E, 68.9 feet, scribed EC 1/16S28BT. Painted blazes red and 6" red band around. Placed 54-3s and 54-4s on BTs. Placed brass washer stamped PLS 1051 on foot blazes. Placed 54-2 and 54-4 on steel fence post 4' South and 54-2 and 54-9 on steel fence post 4' West of corner. Placed 54-5 on tree 10' East of corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Dan T. Rowland

October 16, 1978

Office of... County Surveyor... County of... Union

State of... Oregon... I hereby certify that the within instrument was filed in this office for record on the... 20... day of... November... 1978

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____
GPO 759-509

Date Filed _____

By _____

File No. 88-83R