


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None .

Index File NO. T-19



Description of corner evidence found:

None .

Description of monument and accessories established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" x 30" galvanized pipe and brass cap marked: Set pipe 26" in the ground. No rocks in the area.

From which by magnetic declination of N20°E:
A 9" Tamarac bears N75°E., 12.4 ft. scribed CL/4 S26 BT.
A 11" Fir bears N34°W., 13.8 ft. scribed CL/4 S26 BT.

Painted blazes red and 6" red band around.
Placed 54-3, 54-9s and brass washers stamped PLS 1051 on BTs.
Placed 54-2 and 54-9 on steel fence post 5' west and 54-2 on steel fence post 5' north of the corner.

T4N R40E
CL/4 —+— S26
OR PLS 1051
1981

I hereby certify that the above corner monument was established as herein described.

Witnesses: Daniel Rowland
Beverly Weaselhead

June 17, 1981

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

**OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051**

Office of.....County.....Surveyor..... County of.....Union.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 24 day of.....August....., 1981.

HOWARD L. PERRY
(COUNTY OFFICIAL)

by Ray L. Daniel
(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date ★ GPO-798-276

Date Filed _____

By _____

File No. 93-832