

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-19


History of original corner establishment:

Corner was established by Frank W. Campbell under G. L. O. contract No. 507, dated June 28, 1884

Set a fir post 3" square 3 ft. long, 24" in the ground for ¼ sec cor mkd. ¼ S on N face from which:

A fir 18 ins. diam. bears North 17 lks. dist., mkd. ¼ S BT.

A fir 18 ins. diam. bears S 10° W., 19 lks. dist., mkd. ¼ S BT.



Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner

Set 2½-inch brass cap on 2-inch iron pipe, 31 inches long, 6 inches above ground with a 6 ft. steel fence post alongside with sign 54-4 attached.

A 7" fir bears S 82° E, 23.7 ft. dist., mkd. ¼ S 35 BT.

A 9" fir bears N 20° E, 19.3 ft. dist., mkd. ¼ S 26 BT.

Monument marked:


T 4 N R 40 E

S 26

¼ S 35

RPE 2808

1976



Office of Surveyor County of Union

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 26 day of August, 1976.

..... by

(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	<u>109-83R</u>