


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-17

History of original corner establishment:

Corner was originally established under G. L. O. contract No. 507 by Frank W. Campbell on August 12, 1884. Surveyors General's notes state: "Set post 3 ins. square 3 ft. long 24" in ground for 1/4 Sec corner marked 1/4S on W. face; from which a spruce 10 ins. diam. bears N45°W., 8 lks. dist. marked 1/4S BT. A spruce 8 ins. diam bears S70°E., 18 lks. dist. marked 1/4S BT.



Description of corner evidence found:

Found no trace of record post or BTs.
The west BT was marked 1/4 cor. with red paint.

Description of monument and accessories established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" x 30" galvanized pipe and brass cap marked: Set pipe 25" in the ground. No rock in the area.

From which by magnetic declination of N20°E:

A 9" Tamarac bears N73°E., 27.4 ft. scribed 1/4 S35 BT.

A 24" Fir bears N48°W., 30.9 ft. scribed 1/4 S34 BT.

Painted blazes red and 6" red band around.

Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BTs.

Placed 54-2 and 54-4 on steel fence post 5' east and 54-2 on steel fence post 5' north of the corner.

T4N R40E
1/4

S34 + S35

OR PLS 1051
1981

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Beverly Weaselhead

June 24, 1981

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of...County..Surveyor..... County of..Union.....

State of...Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 24 day of August, 19.81

HOWARD L. HERRY
(COUNTY OFFICIAL)

by *Harvey J. Langley*
(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____
Date Filed _____
By _____
File No. 111-83R