


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-21

History of original corner establishment:

Corner was originally established under G. L. O. contract number 507 by Frank W. Campbell on August 10, 1884. Surveyor Generals notes state: "Set a tamarack post 3 ft. long, 3 ins. square 18 ins. in the ground for 1/4 sec. cor., marked 1/4 S on W. face, from which a tamarack 6 ins. in diam. bears S80°W., 7 lks. dist. marked 1/4S BT. A tamarack 8 ins. in diam. bears N50°E., 18 lks. dist. marked 1/4S BT."



Description of corner evidence found:

Found no trace of record post or BTs. Corner falls near several small dead tamaracs. Corer would be about 27 feet north of surveyed position if measured from the found section corner to the north.

Description of monument and accessories established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" X 30" galvanized pipe and brass cap marked:

Set pipe 20" in the ground and mound of stone around to cap.

From which by magnetic declination of N20°E:

A 12" fir, bears N28°E., 16.5 ft. scribed 1/4 S36 BT.

A 21" tamarac bears N12°W., 46.8 ft. scribed 1/4 S35 BT.

Painted blazes red and 6" red band around. Placed 54-3s, 54-4s, and brass washers stamped PLS 1051 on the BTs. Placed 54-4 on a steel fence post 5' north of the corner.

T4N R40E
1/4
S35 + S36
OR PLS 1051
1981

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Troy Phillips

July 28, 1981

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County Surveyor..... County of..... Union.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 24 day of..... August....., 1981.

HOWARD L. PERRY
(COUNTY OFFICIAL)

by Harry J. Langhitt
(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date received _____

☆ GPO-798-276

Date Filed _____

by _____

File No. 113-83R