
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established under G. L. O. contract Number 507 by Frank W. Campblell on Auguast 8, 1884. Surveyor General's notes state: "Set a basalt stone 14x12x6 ins. 10 ins in the ground for corner to Sec.'s 1, 2, 35 and 36 marked with 5 notches on W. and 1 notch on E edges; from which a pine 24" diam. bears N60°W., 130 lks. dist. marked T4NR40ES35 BT. No other trees convenient. Raised mound of stone alongside in thick brush. "



Description of corner evidence found:

Found no trace of record stone or Pine BT. Computed position falls in very thick brush and rocky area.

NOTE: From Reference Monument computed corner position is:

S 33° 58' 46" W, 267.92 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

For corner control set reference monument at temporary position. Set 2 1/2" x 30" aluminum pipe and cap marked: Set pipe 10" in the ground to bedrock and mound of stone around to cap.

From which by magnetic declination of N20°E: A 30" Fir bears S25 1/2°W., 243.0 ft. scribed T4NR40E RM BT. A 16" pine bears N59°W., 82.8 ft. scribed T4NR40E RM BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s, and brass washers stamped PLS 1051 on BTs. Placed 54-4 on steel fence post 5' north of the monument.

T4N R40E REF. MONUMENT OR PLS 1051 1981

No. 183-83R

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OCT. 17, 1975 BARRY B. BARBOUR

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland Troy Phillips

July 28, 1981

Office ofCounty Surveyor	office
for record on the 24 day of August 19.81 HOWARD FERRY by John Johnson (COUNTY OFFICIAL)	UNION COUNTY SURVEYOR
Form R6-7100-57 (9/71)	Date Received \$\prim \text{GPO} - 798-276
	ty