

T4S 33 1/2 N19

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 1/2 E., Willamette Meridian, Oregon

CHAINS

(Remonumenting corners established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 13, 14, 23, and 24, determined at
record bearing and distance from the remains of the
original bearing trees:

A pine snag, 15 ins. diam., bears N. 36° E., 12
lks. dist., with scribe marks T4S R33 1/2 E S13
visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, in a mound of stone, 2 ft. base, to top,
with brass cap mkd.

T 4 S R 33 1/2 E
S 14 S 13
S 23 S 24
1977

from which new bearing trees

A lodgepole pine, 10 ins. diam., bears N. 77° E.,
110 lks. dist., mkd. T4S R33 1/2 E S13 BT.

A lodgepole pine, 8 ins. diam., bears S. 48° E.,
148 lks. dist., mkd. T4S R33 1/2 E S24 BT.

A lodgepole pine, 9 ins. diam., bears S. 83° W.,
77 lks. dist., mkd. T4S R33 1/2 E S23 BT.

A fir, 9 ins. diam., bears N. 29° W., 160 lks.
dist., mkd. T4S R33 1/2 E S14 BT.

Set a 5 ft. steel fence post alongside iron post.

Corner is located 15 lks. east of gravelled road, 15 lks.
wide, bears N. and S.

The 1/4 sec. cor. of secs. 14 and 23, monumented with the
original unmarked basalt stone, 16 x 12 x 6 ins., loosely
set in a mound of stone, 2 ft. base, 6 ins. high, from
which the only remaining original bearing tree:

A ponderosa pine, 22 ins. diam., bears S. 56° E.,
152 lks. dist., with fragmentary scribe marks
visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins.
in the ground, to solid rock, and in a mound of stone,
3 ft. base, to top, with brass cap mkd.

T 4 S R 33 1/2 E
1/4 S 14
S 23
1977

from which a new bearing tree

A ponderosa pine, 13 ins. diam., bears N. 48° W.,
121 lks. dist., mkd. 1/4 S14 BT.

**UNION COUNTY
SURVEYOR**

Date Received 3/15/12

Date Filed 3/15/13

By J. G. S. DEPUTY

File No. 385-201312

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 33 $\frac{1}{2}$ E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

UNION COUNTY SURVEYOR	
Date Received	<u>3/15/13</u>
Date Filed	<u>3/15/13</u>
By	<u>J. H. S. L.</u> DEPUTY
File No.	<u>385-2013R</u>