

T. 4 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 4 south, range 33½ east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

South Boundary, T. 4 S., R. 33½ E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The ¼ sec. cor. of secs. 2 and 35, on the S. bdy. of the
Tp., determined at record distance from the remains of
the original bearing trees:

A sawed ponderosa pine stump, 30 ins. diam., bears
N. 44° W., 94 lks. dist., with healed blaze.

A ponderosa pine, 26 ins. diam., bears S. 28° E.,
27 lks. dist., with scribe marks ¼ S visible on
open blaze. (Record, S. 7° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.
in the ground, to solid rock, and in a mound of stone, 3
ft. base, to top, with brass cap mkd.

T 4 S R 33½ E
¼ S 35
S 2
T 5 S
1977

from which a new bearing tree

A ponderosa pine, 13 ins. diam., bears N. 5° E.,
169 lks. dist., mkd. ¼ S35 BT.

East Boundary, T. 4 S., R. 33½ E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the
Tp., monumented with the original unmarked basalt stone,
15 x 15 x 6 ins., firmly set 6 ins. in the ground, from
which the remains of the original bearing trees:

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 387-2013R