


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. <sup>A</sup> 7-17

History of original corner establishment:

In 1881, under GLO Contract No. 410, George S. Pershin set a stone 16x10x5, from which an 8" Pine bears N69°W, 68 lks.; a 10" Pine bears S51°W, 89 lks.; and a 24" Pine bears S21°E, 136 lks.



Description of corner evidence found:

No corner monument found.

Bearing tree found:

A 3 1/2" P. Pine stump 6 ft. high, bears S21°E, 89.8 ft. to face of blaze, scribing visible "4S R33E S2".

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2"x30" aluminum capped aluminum pipe rising 14" in mound of stone and earth. Cap stamped:

New BT's:

- A 5" W. Larch bears N66 1/4°W, 60.6 ft., scribed "X" BT.
- An 1 1/2" P. Pine bears N47°E, 112.8 ft., scribed T3S R33E S35 BT.
- A 5" W. Larch bears S31°E, 157.9 ft., scribed "X" BT.
- A 15 1/2" W. Larch bears S57°W, 113.5 ft., scribed T4S R33E S3 BT.

T3S R33E
S34   S35
S3   S2
T4S
1984
RLS 1848

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 1/2°E

Witness: G. Arrand

Set metal fence post 4 ft. north of corner.

From intersection of 2110-220 & 2110-049, SW BT is visible 200 ft. NE.

I hereby certify the above described corner monument and/or accessories was established as described on May 22, 1984.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 13, 1979  
B. A. SUTTON  
1848

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY  
SURVEYOR**

---

Date Received 7-2-84  
☆ GPO-700-278

Date Filed 7-3-84

By G. LANGLITZ, DEPUTY

File No. 881-84 R