

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-1
A-25


History of original corner establishment:

Corner established by General Land Office contract survey

The original notes state:

Said point is 68.30 lks north of corner sections 6, 7, 1, and 12, T4S R33½ and 34E.

Set basalt stone 30 x 15 x 6", 23" in ground for corner to T4S R33½ and 34E marked with 6 notches on the south and west edges and raised a mound of stone 3 ft. high and 5 ft. base alongside. Then continue line west on south boundary of section 31.



Description of corner evidence found:

Found ~~corner~~ ~~at~~ ~~stone~~.

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 30" galvanized pipe with an eight inch plate welded to bottom and bronze cap on top. The hole was back filled with stone and tamped soil and I raised a mound of stone around pipe.

I stamped the disk.

From the monument the original bearing trees were; (none).

I established the following new bearing trees;

Yellow Pine 16" dia N60°W at a distance of 53.5 ft. and scribed T3S R34E S31 BT

Yellow Pine 10" dia S66°W at a distance of 62 ft. and scribed T4S R33½E S1 BT

Yellow Pine 9" dia S7°E at a distance of 101.2 ft. and scribed T4S R34E S6 BT

The distance measured to center of respective trees on level. I placed bearing tree signs on the new bearing trees and painted stripe around trees. I placed a steel fence post with USFS sign 54-4 attached near the corner.

CCR
T3S T4S
R33½E R34E

S 31

S 1 | S 6

ORE LIC 381
1970

Office of County Surveyor County of Union
 State of Oregon I hereby certify that the within instrument was filed in this office
 for record on the 18 day of August, 1970, at 5 o'clock P.m., (signed)
 County Surveyor by Jamuel D. Drey
 (COUNTY OFFICIAL) (SHERIFF)


| | |
|-------------------------|-------|
| UNION COUNTY SURVEYOR | |
| Date Received _____ | _____ |
| Date Filed _____ | _____ |
| By _____ | _____ |
| File No. <u>362-84R</u> | _____ |

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. A-25¹

History of original corner establishment:

In 1882, under GLO Contract 451, Rufus S. Moore set a stone 30x15x6 with 6 notches on the south and west edges and raised a mound of stone 3 ft. high and 5 ft. base alongside.



Description of corner evidence found:

Found BLM 3" brass capped iron pipe rising 16" in mound, stamped:
Cap is not stamped as original certificate shows.

COR
T3S R33 1/2E
T4S R33 1/2E

Bearing trees found:

- A 20" P. Pine bears N62°W, 53.5 ft.
(Original certificate reads N60°W.)
- A 12" P. Pine bears S36°W, 85.4 ft.
(Original certificate reads S66°W, 62 ft.)
- A 12" P. Pine bears S11°E, 101.2 ft.
(Original certificate reads S7°E.)

S31
S1 | S6
ORE LIC 381
1970

Found metal fence post 4 ft. west of corner

Description of monument and accessories established to perpetuate the original location of this corner:

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 1/2°E
Witness: D. Scott

Approximately 400 ft. north of 2100-102, corner is 300 ft. west of 21.

I hereby certify the above described corner monument and/or accessories was established as described on May 8, 1984.

| | |
|------------------------------|---------------------------|
| UNION COUNTY SURVEYOR | |
| Date Received | <u>7-2-84</u> |
| Date Filed | <u>7-3-84</u> |
| By | <u>G. LANGLITZ DEPUTY</u> |
| File No. | <u>918-84 R</u> |

| | |
|---|--|
| REGISTERED PROFESSIONAL LAND SURVEYOR | |
|  | |
| OREGON JULY 13, 1979 B. A. SUTTON 1848 | |

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)