
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established by Rufus Moore in 1882. Set a basalt stone 15 x 12 x 7 ins 10 ins in the ground for cor to secs 2 & 3 with 2 notches on the $\rm E$ and 4 notches on W edges from which:

a pine 14 ins. diam bears S40°E, 9 lks dist. marked

T4S R34E S2 BT. a pine 14 ins. diam bears S32°W, 288 lks dist. marked T4S R34E S3 BT.



Description of corner evidence found:


A 24' diameter, 50" high, scribed Ponderosa Pine stump bears S40°E, 5.9' being used for a fence corner.

A dead and down scribed Ponderosa Pine bears S32° W, 190.1'. An unofficial scribed Ponderosa Pine 16' in diameter bears N86°30'E, 33.4'. The scribe has been sealed over at one time and opened to reveal scribing which appears to be 4S R34E S2. Portions of the blaze above and below this scribing remain sealed over.

No trace of the original stone monument was found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2" x 30" galvanized iron pipe with 2½" brass cap marked: Pipe is set into ground 12" in a stone mound. A steel fence post is set 5' from the brass cap with a USFS Land Survey Monument sign attached. The brass cap is set at the surveyed point of intersection which was found to be N1°04'33"E, 1.24' from the original closing corner point as established from the original bearing trees.



Bearing Trees:

The unofficial bearing tree described above is accepted as a bearing tree The unofficial bearing tree described above is accepted as a bearing tree and bears N86°30'E, 33.4' from the brass cap. The tree is painted with a red band and has USFS Land Survey Monument and Bearing Tree signs attached. An 8" Ponderosa Pine bears S17°45'W, 51.4' from the brass cap scribed T4S R34E S3 CC BT on a single blaze. The tree is painted with a red band and has USFS Land Survey Monument and Bearing Tree signs attached. A 3/4" aluminum washer stamped RLS 852 is nailed between the letters B and T.

I hereby certify the above corner point was perpetuated as hereon described on August 21, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR

David L. Haddock OREGON

	JULY 12 1050
	DAVID L. HADDOGE
	DAVID L. HADDOCK 852
Office of County of	
State of I hereby certify that the within instrument was filed in this off	ice
for record on the day of.	

UNION COUNTY SURVEYOR (COUNTY OFFICIAL (DEPUTY) Form R6-7100-57 (9/71) Date Received 10-2-86

SEE SURVEY

35-86

\$ GPO-798-276

Date Filed 10-13-86

File No. 178-86