


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. C-05

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 18x7x7, from which a 36" Pine bears N55°W, 179 lks. and an 11" Pine bears S73°E, 106 lks.



Description of corner evidence found:

Found a 30" dead standing Pine bears N55°W, 118.1 ft., 10 ft. high stump, blaze and scribing visible.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2" x 30" aluminum capped aluminum pipe rising 18" in mound, stamped:

T4S	R34E
1/4	
S6	S5
1984	
RLS 1848	

New BT's:

- A 7.5" P. Pine bears N49 3/4°W, 49.3 ft., scribed 1/4 S6 BT.
- A 7.5" P. Pine bears N 5 3/4°E, 75.4 ft., scribed 1/4 S5 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Set metal fence post 6 ft. north of corner in mound.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From 2105-101, northerly along 2105-104 0.4 mi. Original BT stump is on the right side of the road. Corner 120 ft. east.

I hereby certify the above described corner monument and/or accessories was established as described on May 15, 1984.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

B. Sutton

OREGON
JULY 13, 1979
B. A. SUTTON
1848

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 7-2-84

Date Filed ☆ GPO-798-276 7-3-84

By G. LANGLITZ DEPUTY

File No. 924-84 R