

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Original corner established in 1882 by Rufus Moore.

Set a post 3' long, 3" square, 24" in the ground for $\frac{1}{4}$ sec. Corner marked: $\frac{1}{4}$ S on north face. From which:

A 9" fir bears: N 30° W, 31 links. (20.5')

A 10" fir bears: S 62° E, 12 links. (7.9')



Description of corner evidence found:

A dead and down fir bears: N 30° W, 20.5' with plainly visible scribing.

A dead and down fir bears: N 62° E, 7.9'. Scribing is visible on a 2" x ~~12~~ 30" piece of the tree.

UNION COUNTY SURVEYOR

Date Received 10-2-86

Date Filed 10-13-86

By G. LANGLIZ, DEPUTY

File No. 169-86 R

SEE SURVEY
35-86

Description of monument and accessories established to perpetuate the original location of this corner:


Set a 2"x 30" galvanized Iron pipe with a 2 1/2" brass cap marked: Pipe is set 24" in ground in a stone mound.

New Bearing Trees:

A 7" Fir bears: N 56° 45' W, 7.8', scribed " $\frac{1}{4}$ S3 BT" on a single blaze.

An 8" Fir bears: N 63° 15' E, 14.0'; scribed " $\frac{1}{4}$ S2 BT", on a single blaze. A 3/4" aluminum washer marked " RLS 852" is nailed between the letters B and T, on each tree. A 6" red band is painted on each tree and a U.S.F.S. Bearing Tree and Land Survey Monument sign is attached.

A steel fence post is set 5' from the brass cap with a U.S.F.S. Survey Monument sign attached.



I hereby certify the above corner point was perpetuated as hereon described on July 15, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR

David L. Haddock

OREGON
JULY 12, 1988
DAVID L. HADDOCK
852

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)