


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-17

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 20x20x15, from which a 12" Pine bears S68°W, 169 lks.; a 40" Pine bears S76°E, 60 lks.; and an 18" Fir bears N59°E, 42 lks.

Index File No. E-25



Description of corner evidence found:

Found original stone 16x16x10, one side having 5 faint notches, the other side having one notch.

Found a 25.5" P. Pine bearing S66°W, 113.2 ft., blaze visible. Did not open.


UNION COUNTY SURVEYOR
Date Received <u>7-2-84</u>
Date Filed <u>7-3-84</u>
By <u>G. LANGLITZ DEPUTY</u>
File No. <u>922-84 R</u>

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2" x 30" aluminum capped aluminum pipe stamped;
Original stone buried on north side.

New BT's:

- An 8" P. Pine bears N8 1/4°W, 40.9 ft., scribed T4S R33 1/2E S1 BT.
- An 8.5" P. Pine bears N65 1/2°E, 17.9 ft., scribed T4S R34E S6 BT.
- An 8.5" P. Pine bears S48°E, 147.4 ft., scribed T4S R34E S7 BT.



Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Set metal fence post 4 ft. north of corner.

Compass Declination: 19 1/2°E

Witness: D. Scott

From 2100-146, south .6 mi. on Rd. 21. There is a tag and a section board on a tree on the left side of the road. Corner is about 300 ft. west of the road.

I hereby certify the above described corner monument and/or accessories was established as described on May 10, 1984.

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>B. A. Sutton</i>
OREGON JULY 13, 1979 B. A. SUTTON 1848

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

E-1