


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner was established by Rufus Moore, in 1882.

Set a basalt stone 32"x10"x4", 24" in ground for 1/4 sec. Corner marked 1/4 on west face. From which:

- A 5" Pine bears S 48°E, 9 links.(5.9')
- A 4" Pine bears N 21°W, 22links.(15.2')



Description of corner evidence found:

A stone 32"x10"x4" marked 1/4 on one end with the other end embedded in the ground.

A 14" Ponderosa Pine snag with 1/4 S scribe visible bears S 48°E, 5.9 feet.

UNION COUNTY SURVEYOR

Date Received 10-2-86

Date Filed 10-13-86

By G. LANGRISH, DEPUTY


File No. 160-86 R

SEE SURVEY 35-86

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x 30" galvanized iron pipe with 2 1/2" brass cap marked:

Pipe is set in ground 24" in a mound of stones. Stone with 1/4 mark is placed along side pipe.



New Bearing Trees:

- A 13" Ponderosa Pine bears N 42°15'W, 13.8' scribed "1/4 S 2 B.T." on a single blaze.
- A 15" Fir bears S 54°00'W, 16.8' scribed "1/4 S 11 B.T." on a single blaze.
- A 3/4" aluminum washer marked "RLS 852" is nailed between the letters B and T. on each tree. Each tree is painted with a 6" red band and has a U.S.F.S. Bearing Tree and Land Survey Monument sign attached.

A steel fence post is set 5' from the brass cap with a U.S.F.S. Land Survey Monument sign attached.

I hereby certify the above corner point was perpetuated as hereon described on July 17, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR

David L. Haddock

OREGON
JULY 12, 1988
DAVID L. HADDOCK
852

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL) (DEPUTY)