


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established in 1882 by Rufus Moore. Set a basalt stone 14 x 9 x 7 ins, 10 ins in ground for corner to sections 1, 2, 11, and 12 marked with 5 notches on south and 1 notch on east edges, from which:

A 42" Pine bears N28°E, 228 links.



Description of corner evidence found:

Stone with 5 notches in a small stone mound.

A dead and down Pine with scribing bears N28°E, 150.5'.

UNION COUNTY SURVEYOR

Date Received 10-2-86


Date Filed 10-13-86

By G. LANGLITZ, DEPUTY

File No. 159-86 R

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2" x 30" galvanized iron pipe with 2 1/2" brass cap marked: Pipe is set in ground 12" in a mound of stone. Stone with 5 notches is placed alongside the pipe. A steel fence post is set 5' from the brass cap with a USFS Land Survey Monument sign attached.



New Bearing Trees:

A 20" Ponderosa Pine bears N9°45'W, 76.4' scribed T4S R34E S2 BT on a double blaze. A 13" Ponderosa Pine bears S64°15'W, 51.3' scribed T4S R34E S11 BT on a double blaze. A 15" Ponderosa Pine bears N44°30'E, 120.2' scribed T4S R34E S1 BT in a single blaze. A 13" Ponderosa Pine bears S17°45'E, 121.1' scribed T4S R34E S12 BT in a single blaze. A 3/4" aluminum washer stamped RLS 852 is nailed between the letters B and T on each tree. A 6" red band is painted around each tree and USFS Bearing Tree and Land Survey Monument signs attached.

I certify the above corner point was perpetuated as hereon described on July 16, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR

David L. Haddock

**OREGON
JULY 12, 1968
DAVID L. HADDOCK
852**

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)