


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established in 1882 by Rufus Moore. Set a basalt stone 20 x 7 x 7 ins 15 ins. in ground for 1/4 sec. cor. marked 1/4 on W. face, and raised a mound of stone alongside.




Description of corner evidence found:

A 20" x 7" x 7" stone with 1/4 chiseled on face in a mound of stones.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2" x 30" galvanized iron pipe with 2 1/2" brass cap marked: Pipe is set 8" into ground with a mound of stone built up around it. A steel fence post is set 5' from the brass cap with a USFS Land Survey Monument sign attached.



New witness trees:

A 20" Ponderosa Pine bears S53°45'E, 185.4' scribed 1/4 S12 BT in a single blaze. A 14" Ponderosa Pine bears S20°15'W, 173.3' scribed 1/4 S11 BT in a single blaze. A 3/4" aluminum washer stamped RLS 852 is nailed between the letters B and T on each tree. Each tree is painted with a 6" red band and has USFS Bearing Tree and Land Survey Monument signs attached.

I hereby certify the above corner point was perpetuated as hereon described on August 15, 1986.

August

SEE SURVEY  
35-86

**UNION COUNTY SURVEYOR**

---

Date Received 10-2-86

Date Filed 10-13-86

By G. LANGRISH DEPUTY

File No. 155-86R

**REGISTERED PROFESSIONAL LAND SURVEYOR**

David L. Haddock

**OREGON**  
JULY 12, 1968  
**DAVID L. HADDOCK**  
852

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)