
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established by Rufus Moore in 1882. Set a basalt stone 24 x 13 x 13 ins, 12 ins in ground for corner to sections 11, 12, 13, and 14, marked with 4 notches on south and 1 notch on east and raised a mound of stones along side from which: An 8" Pine bears N32°E, 363 links.



Description of corner evidence found:

A mound of stone with a $24 \times 13 \times 13$ inch stone in center. Stone is vesicular lava and no marks are visible.

A 24" Ponderosa Pine bears N32°E, 239.5'. A scribe of the correct size is grown over.

Date Received 10-2-86

Date Filed 10-13-86

By G. LANGLITZ DEPUTY

See Survey 35-86

Description of monument and accessories I established to perpetuate the File No. original location of this corner:

Set 2" x 30" galvanized iron pipe with $2\frac{1}{2}$ " brass cap marked: Pipe is set in ground 12" in a mound of stone. Original stone is placed alongside the pipe. A steel fence post is set 5' from the brass cap with a USFS Land Survey Monument sign attached.

T45 R34E

511 | S12

514 | S13

PLS 852

1986

New Bearing Trees:

A 9" Ponderosa Pine bears S84°00'W, 129.4' scribed T4S R34E S14 BT on a double blaze. A 8" Ponderosa Pine bears S86°00'E, 118.2' scribed T4S R34E S13 BT on a single blaze. A 13" Ponderosa Pine bears N72°45'W, 192.7' scribed T4S R34E S11 BT on a single blaze. Each tree has a 3/4" aluminum washer stamped RLS 852 nailed between the letters B and T. Each tree is painted with a 6" red band and has USFS Bearing Tree and Land Survey Monument signs attached.

I hereby certify the above corner point was perpetuated as hereon described on July 16, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 12, 1968
DAVID L. HADDOCK

Office of	County of
State of , I hereby certify tha	t the within instrument was filed in this office
for record on the day of	, 19
(COUNTY OFFICIAL)	(DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO---798-276