


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner was established in 1882 by Rufus Moore.

Set a basalt stone 23 x 20 x 7 ins 15 in in ground for 1/4 sec. cor. marked 1/4 on W. face and raised a mound of stone alongside.




Description of corner evidence found:

A stone 23" x 20" x 7" marked 1/4 on the face. Stone was at the very bottom of a large rock crib which was about 8' east of an old north-south fence line.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 2" x 30" galvanized iron pipe with 2 1/2" brass cap marked: Pipe is set in ground 8" and a stone mound raised around the pipe. A steel fence post is set 5' from the brass cap with a USFS Land Survey Monument sign attached.



New Bearing Trees:

A 14" Ponderosa Pine bears N86°45'E, 30.2' scribed 1/4 S12 BT in a single blaze. A 12" Ponderosa Pine bears S17°15'E, 116.6' scribed 1/4 S13 BT in a single blaze. A 3/4" aluminum washer stamped RLS 852 is nailed between the letters B and T on each tree. A 6" red band is painted around each tree and USFS Bearing Tree and Land Survey Monument signs attached.

I hereby certify the above corner point was perpetuated as hereon described on August 16, 1986.

**UNION COUNTY SURVEYOR**

---

Date Received 10-2-86

Date Filed 10-13-86

By G. LANGLITZ DEPUTY

File No. 152-86R

**REGISTERED PROFESSIONAL LAND SURVEYOR**

*David L. Haddock*

**OREGON**  
JULY 12, 1968  
**DAVID L. HADDOCK**  
852

SEE SURVEY 35-86

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)