


LAND CORNER RECORD

5680-2

1. T 4S R 34E No. N1 Cor. Sec. Mer. Will State Oregon (Rec. Angular) N. F. Wallowa Whitman Dist. LaGrande

2. Corner Status

N-1



3. Original Description \_\_\_\_\_ Vol. \_\_\_\_\_ Page \_\_\_\_\_ Where Recorded \_\_\_\_\_

4. Description of Corners: None Found

5. Investigation Notes:

1 BT-22" DF Blowdown Dead  
Location poster on this one.

1 BT-26" PP Alive

1 BT-30" PP Alive.

I painted BTs red. Located in heavy  
timber. I put new location poster on  
30" PP

7. Photo Identification

Photo No. \_\_\_\_\_

Ident. By: \_\_\_\_\_

8. Plane Coordinate Position Data

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

Field Book No. \_\_\_\_\_

Where Filed \_\_\_\_\_

9. Evaluation

Authentic \_\_\_\_\_

Needs Verif. \_\_\_\_\_ Monument \_\_\_\_\_

Re-estab. \_\_\_\_\_ Survey \_\_\_\_\_

Land Status \_\_\_\_\_

6. Signed S. Kelly J. Wick Title For. & D.R Date 11-10-65

**UNION COUNTY SURVEYOR**

---

Date Received \_\_\_\_\_

Date Filed 12-21-87

By G. LANGLITZ, DEPUTY

File No. 290-87R

N-1

T4S34N01

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

A pine snag, 9 ins. diam., bears S. 83° E., 25  
lks. dist., with healed blaze. (Record,  
S. 89° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 4 S  
¼  
R 33½ E | R 34 E  
S 25 | S 30  
1977

from which new bearing trees

A lodgepole pine, 8 ins. diam., bears S. 36° E.,  
81 lks. dist., mkd. ¼ S30 BT.

A lodgepole pine, 8 ins. diam., bears N. 39° W.,  
22 lks. dist., mkd. ¼ S25 BT.

Deposit corner stone and set a 5 ft. steel fence  
post alongside iron post.

T4S34T01

The cor. of secs. 13, 18, 19, and 24, on the E. bdy. of  
the Tp., monumented with the remains of the original  
corner tree, a root hole, with a down and decayed fir  
alongside, size indeterminate, with scribe marks R33E  
S18 visible on open blaze and scribe marks R33½E S13  
visible on another open blaze, from which the remaining  
original bearing tree:

A pine, 30 ins. diam., bears N. 48° E., 23 lks.  
dist., with scribe marks R33E S18 visible on  
open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 4 S  
R 33½ E | R 34 E  
S 13 | S 18  
S 24 | S 19  
1977

from which new bearing trees

A pine, 11 ins. diam., bears S. 36° E., 17 lks.  
dist., mkd. T4S R34E S19 BT.

A grand fir, 15 ins. diam., bears S. 84° W., 75½  
lks. dist., mkd. T4S R33½E S24 BT.

A grand fir, 14 ins. diam., bears N. 11° W., 29  
lks. dist., mkd. T4S R33½E S13 BT.

Set a 5 ft. steel fence post alongside iron post.

T4S34N01

UNION COUNTY  
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By [Signature] DEPUTY

File No. 388-2013

Subdivisions, T. 4 S., R. 33½ E.,  
Willamette Meridian, Oregon