

LAND CORNER RECORD

5680-2

1. T AS R3 R34E No. 33 Cor. 1/4 Mer Will State Oregon N.F. Wallowa Whitman Dist. LaGrande

2. Corner Status

3. Original Description \_\_\_\_\_ Vol. \_\_\_\_\_ Page \_\_\_\_\_ Where Recorded \_\_\_\_\_

4. Description of Corners: Rocks 10-12"  
Ground level - Poor condition  
A pile of rocks that have fallen over.

5. Investigation Notes: R


2 BTs. (1) 26" PP Alive. Approx. 54' E. of  
corner

possible BT → (2) 36" PP - Alive. Approx 149' from 1/4  
cor. at a north BRng.

there is a drainage to the west of  
the corner. Road S-214 is approx 550'  
west of BT with location poster on it.  
Corner + BTs painted red. Ashield was put  
on 36" PP - location poster on 26" PP.

6. Signed S. Kelly J. Wick Title For + DR. Date 11-9-65

R-3



1/4 corner

7. Photo Identification

Photo No. UBM-0-4-3

Ident. By: S. Kelly  
11-9-65

8. Plane Coordinate Position Data

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

Field Book No. \_\_\_\_\_

Where Filed \_\_\_\_\_

9. Evaluation

Authentic \_\_\_\_\_

Needs Verif. \_\_\_\_\_ Monument \_\_\_\_\_

Re-estab. \_\_\_\_\_ Survey \_\_\_\_\_

Land Status \_\_\_\_\_

<b>UNION COUNTY SURVEYOR</b>	
Date Received _____	
Date Filed <u>12-21-87</u>	
By <u>G. LANGLITZ, DEPUTY</u>	
File No. <u>294-87R</u>	

70-1-W

T4S34R03

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 29° E., 208 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R34E visible on open blaze.

A pine snag, 38 ins. diam., bears S. 52° W., 144 lks. dist., with scribe marks T4S R34E S30 visible on open blaze.

A pine snag, 34 ins. diam., bears N. 61° W., 325 lks. dist., with scribe marks 4S R34E visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E  
S 19 | S 20  
S 30 | S 29  
1977

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears N. 34° E., 27 lks. dist., mkd. T4S R34E S20 BT.

A grand fir, 8 ins. diam., bears S. 27° E., 106 lks. dist., mkd. T4S R34E S29 BT.

A grand fir, 7 ins. diam., bears S. 24° W., 47 lks. dist., mkd. T4S R34E S30 BT.

A lodgepole pine, 12 ins. diam., bears N. 66½° W., 31½ lks. dist., mkd. T4S R34E S19 BT.

Set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 19 and 30, monumented with the original basalt stone, 18 x 12 x 5 ins., loosely set in a mound of stone, 2 ft. base, 6 ins. high, mkd. ¼ on W. face, from which the original bearing trees:

A ponderosa pine, 35 ins. diam., bears N. 25° E., 226 lks. dist., with healed blaze.

A ponderosa pine, 25 ins. diam., bears S. 70° E., 84 lks. dist., with scribe marks ¼ S visible on open blaze. (Record, 81 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E  
¼ S 19  
S 30  
1977

UNION COUNTY  
SURVEYOR

Date Received

3/15/13

Date Filed

3/15/13

By

*M. S. DEWITT*

File No.

389-2013R

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone and set a 5 ft. steel fence  
post alongside iron post.

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>3/15/13</u>
Date Filed	<u>3/15/13</u>
By	<u><i>[Signature]</i> DEPUTY</u>
File No.	<u>389-2013R</u>