

T4S34R05

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 29° E., 208 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks T4S R34E visible on open blaze.

A pine snag, 38 ins. diam., bears S. 52° W., 144 lks. dist., with scribe marks T4S R34E S30 visible on open blaze.

A pine snag, 34 ins. diam., bears N. 61° W., 325 lks. dist., with scribe marks 4S R34E visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E
S 19   S 20
S 30   S 29
1977

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears N. 34° E., 27 lks. dist., mkd. T4S R34E S20 BT.

A grand fir, 8 ins. diam., bears S. 27° E., 106 lks. dist., mkd. T4S R34E S29 BT.

A grand fir, 7 ins. diam., bears S. 24° W., 47 lks. dist., mkd. T4S R34E S30 BT.

A lodgepole pine, 12 ins. diam., bears N. 66½° W., 31½ lks. dist., mkd. T4S R34E S19 BT.

Set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 19 and 30, monumented with the original basalt stone, 18 x 12 x 5 ins., loosely set in a mound of stone, 2 ft. base, 6 ins. high, mkd. ¼ on W. face, from which the original bearing trees:

A ponderosa pine, 35 ins. diam., bears N. 25° E., 226 lks. dist., with healed blaze.

A ponderosa pine, 25 ins. diam., bears S. 70° E., 84 lks. dist., with scribe marks ¼ S visible on open blaze. (Record, 81 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 34 E
¼ S 19
S 30
1977

T4S34R05

UNION COUNTY  
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 390-2013R