CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner has not been previously set.

DI AGRAH

T4S R35E C N1/16 5 8 Ç 1989 PLS 699

Description of corner evidence found: Corner is being set by this survey.

UNION COUNTY SURVEYOR

Date Received 9-25-89

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 24" aluminum cap, marked as shown in the diagram, 24" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock & earth to be 30" in diameter by 6" high around the monument, from which new BTs are:

11° Douglas-fir bears S89°W, 10.6 feet scribed CN1/16 S8 BT

9" Douglas-fir bears S10° 15'W, 13.6 feet scribed CM1/16 S8 BT Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between the SE and S% corners of Section 7 as shown on MOS 43-76, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet S and 5 feet W of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the S post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on July 18, 1989, I established the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON LELAND LEE MYERS

FILED

IN THE OFFICE OF THE Union COUNTY SURVEYOR THIS ____ DAY OF

Union County Surveyor

USDA-FS Contract No. 04M3-8-6103