


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:  
Corner has not been previously set.

DIAGRAM



Description of corner evidence found:  
Corner is being set by this survey.

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>9-25-89</u>
Date Filed	<u>9-25-89</u>
By	<u>G. LANGRIZ</u>
File No.	<u>183-89 R</u>

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/4" aluminum cap, marked as shown in the diagram, 22" in the ground to hard pan, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock & earth to be 30" in diameter by 6" high around the monument, from which new BTs are:

- 24" Ponderosa pine bears S55° 30'N, 206.0 feet scribed CN1/16 S17 BT
- 22" Ponderosa pine bears S64° 15'E, 254.0 feet scribed CN1/16 S17 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between the SE and S4 corners of Section 7 as shown on MOS 43-76, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet N and 5 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on July 18, 1989, I established the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

*Leland L. Myers*  
OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699

FILED

IN THE OFFICE OF THE Union COUNTY SURVEYOR  
THIS \_\_\_\_ DAY OF \_\_\_\_\_, 19\_\_

Union County Surveyor