

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Jacob C. Cooper, US Deputy Surveyor, during the original survey Contract No. 397 dated July, 1881. Set a post 3 1/4 ft long 3 ins square 18 ins in ground in open sloping hillside for 1/4 sec cor marked 1/4S on E and W faces. No trees near. I raised a mound of stone alongside of post

DIAGRAM

T4S
R34E R35E

1/4
S13 | S18

1976
PLS 644

Corner was monumented by Duane I. Griffith, PLS 644, during a retracement survey dated July, 1976.

(The record does not indicate what was or was not found, but the map of survey shows the corner to have been reestablished by single proportionate measurement.)

Set 1"x30" iron pipe with brass cap marked as shown

Description of corner evidence found:

A 1" galvanized pipe with a 2 1/4" brass cap standing 20" out of the ground in a disturbed rock mound.
No bearing trees were previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Maintained the monument by straightening and improving the mound and establishing 2 references. Improved the existing mound with rock to be 36" in diameter by 14" high around the monument. I do not certify the correctness of this monument by doing this maintenance work.

- No new bearing trees set because no trees are within the allowable limits.
- No. 4 Rebar with a yellow plastic cap marked PLS 699 bears N61°E, 36.1 feet
- Elk enclosure fence corner post with an aluminum washer stamped PLS 699 on a 60d spike in the side of the post bears S50°30'W, 2.1 feet

Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between the SE and S 1/4 corners of Section 7 as shown on MOS 43-76.

Set steel fence posts 5 feet N and 15 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the N post.

UNION COUNTY SURVEYOR
Date Received <u>9-25-89</u>
Date Filed <u>9-25-89</u>
By <u>G. LANGLITZ</u>
File No. <u>185-89 R</u>

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on July 23, 1989, I maintained the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Union COUNTY SURVEYOR
THIS _____ DAY OF _____, 19____

Union County Surveyor

Dependent Resurvey of a Portion of the West Boundary,
T. 4 S., R. 35 E., Willamette Meridian, Oregon

FEET	Along Corral Creek , through dense timber and undergrowth.
320.18	Oregon State Highway No. 244, asphalt surfaced, 40 ft. wide, bears N. 40° E. and S. 40° W.
2644.91	The ¼ sec. cor. of secs. 13 and 18, reestablished by proportionate measurement in 1976, by Duane I. Griffith, Professional Land Surveyor No. 644, recorded as Survey No. 43-76 at the Union County Surveyor's Office, in LaGrande, Oregon, subsequently utilized in 1989, by Leland Lee Myers, Professional Land Surveyor No. 699, recorded as Survey No. 21-89 at the Union County Surveyor's Office in LaGrande, Oregon, and is accepted as the corner. Monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 4 ft. base, to top of brass cap mkd.

T 4 S
1/4
R 34 E | R 35 E
S 13 | S 18
1976
OPLS 644

T4S35 L01

from which the accessories set by Myers in 1989

An aluminum spike and washer, stamped PLS 699, set in a wooden fence post, bears S. 50½° W., 2.1 ft. dist., from which a barbed wire fence extends E., and a woven wire fence extends N. and S. 60° W.

An iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with a yellow plastic cap with illegible marks, bears N. 61° 00' 00" E., 36.20 ft. dist.

Corner is located in open, level land.

The geographic position (NAD 1983 (CORS 96)) of this corner is:

Latitude: 45° 13' 07.384" N. Longitude: 118° 29' 06.731" W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 S., R. 35 E., Willamette Meridian, Oregon

(Restoring the Survey by Rufus S. Moore, in 1882)

From the cor. of secs. 17, 18, 19, and 20, perpetuated in 1976, and in 1985, by Duane I. Griffith, Professional Land Surveyor No. 644, from original evidence, no longer in existence and recorded as Survey No. 43-76 at the Union County Surveyor's Office, in LaGrande, Oregon, monumented with an aluminum post,

UNION COUNTY SURVEYOR	
Date Received	3/8/13
Date Filed	3/8/13
By	<i>[Signature]</i> DEPUTY
File No.	206-2013R