

T4S35L03

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 S., R. 35 E., Willamette Meridian, Oregon

UNION COUNTY SURVEYOR	
Date Received	3/8/13
Date Filed	3/8/13
By	JPL DEERY
File No.	207-20BR

An iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears N. 36° 00' 00" E., 7.90 ft. dist., no cap.

A pine, 22 ins. diam., bears S. 86½° W., 146.7 ft. dist., with fragmentary scribe marks visible on partially healed blaze.

Corner is located on level, open land.

The geographic position (NAD 1983 (CORS 96)) of this corner is:

Latitude: 45° 13' 58.906" N. Longitude: 118° 27' 55.314" W.

Subdivision of Section 18,
T. 4 S., R. 35 E., Willamette Meridian, Oregon.

From the ¼ sec. cor. of secs. 18 and 19.

N. 0° 32' 12" E., on the N. and S. centerline of sec. 18.

Over open, level land.

2649.94

The center ¼ sec. cor. of sec. 18, established in 1976, by Duane I. Griffith, Professional Land Surveyor No. 644, and recorded as Survey No. 43-76 at the Union County Surveyor's Office, in LaGrande, Oregon, utilized in 1989, by Leland Lee Myers, Professional Land Surveyor No. 699, recorded as Survey No. 21-89 at the Union County Surveyor's Office, in LaGrande, Oregon, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 3 ft. base, to top, with a brass cap mkd.

T 4 S R 35 E
C 1/4
S 18
1976
OPLS 644

T4S35L03

from which a new bearing tree

A pine, 16 ins. diam., bears N. 84° W., 31.6 ft. dist., mkd. C 1/4 S18 BT.

No other accessories available.

Corner is located on open level land, and is 5 ft. W. of a dim trail road, 12 ft. wide, bears N. 20° E. and S. 20° W.

The geographic position (NAD 1983 (CORS 96)) of this corner is: