Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 35 E., Willamette Meridian, Oregon

		T. 4 S., R. 35 E., Willamette Meridian, Oregon	
	FEET		
		The geographic position (NAD 1983 (CORS 96)) of this corner is:	
		Latitude: 45° 12' 40.937" N. Longitude: 118° 28' 32.363" W.	
		Continue over open, level land.	
4	1980.0	Dirt road, 14 ft. wide, bears N. 35° E. and S. 35° W.	
5	5081.80	Point selected for the witness cor. for the cor. of secs. 13, 18, 19, and 24, hereinbefore described.	
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
		WC	
		T 4 S R 34 E R 35 E	
		S 13 S 18	74535 Nol
		S 24 S 19	101000
		2005	
		from which	
		A fir, 24 ins. diam., bears S. 69%° E., 19.4 ft. dist., mkd. X at breast height and BT at the base.	
		A spruce, 14 ins. diam., bears S. 7%° W., 32.4 ft. dist., mkd. X at breast height and BT at the base.	
		A fir, 5 ins. diam., bears S. 60½° W., 25.3 ft. dist., mkd. X at breast height and BT at the base.	
		Deposit a magnet in a white plastic case at the base of the stainless steel post.	
	5131.80	True point for the cor. of secs. 13, 18, 19, and 24.	
		From the cor of secs. 17, 18, 19, and 20.	
		N. 0° 7' 45" E., between secs. 17 and 18.	
		Over level land, through scattered timber.	
	2655.42	The ¼ sec. cor. of secs. 17 and 18, perpetuated in 1976 from	
UNION C SURVE		original evidence no longer in existence, and in 1985, by Duane I. Griffith, Professional Land Surveyor No. 644, and recorded as	anM1 8
		Survey No. 43-76 at the Union County Surveyor's Office, in LaGrande, Oregon, subsequently utilized in 1989, by	
Date Received	3/8/13	Leland Lee Myers, Professional Land Surveyor No. 699, recorded as Survey No. 21-89 at the Union County Surveyor's Office in	
Date Filed 3	18/13	IaGrande, Oregon, monumented with an aluminum post,	
	0/		
by <u>JAC</u>	SL-DEA	<u>79</u>	

File No.