

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 S., R. 35 E., Willamette Meridian, Oregon

FEET	<p>2 ins. diam., firmly set, projecting 6 ins. above the ground, in an embedded mound of stone, 3 ft. base, to top, with an aluminum cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>T 4 S</td><td>R 35 E</td></tr> <tr><td>S 18</td><td>S 17</td></tr> <tr><td>S 19</td><td>S 20</td></tr> <tr><td colspan="2" style="text-align: center;">1985</td></tr> <tr><td colspan="2" style="text-align: center;">OPLS 644</td></tr> </table> <p>from which the bearing trees marked by Griffith in 1985</p> <p>A pine, 16 ins. diam., bears N. 45½° E., 79.3 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A pine, 20 ins. diam., bears S. 51¼° E., 45.6 ft. dist., with scribe marks R35E visible on a partially healed blaze.</p> <p>A pine, 17 ins. diam., bears S. 30° W., 54.8 ft. dist., with scribe marks 4S R3 visible on a partially healed blaze.</p> <p>A pine, 24 ins. diam., bears N. 40° W., 22.6 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>Corner is located on level land and is 4 ft. S. of a steel fencepost.</p> <p>N. 89° 11' 50" W., between secs. 18 and 19.</p> <p>Descend moderate W. slope, through scattered timber.</p>	T 4 S	R 35 E	S 18	S 17	S 19	S 20	1985		OPLS 644	
T 4 S	R 35 E										
S 18	S 17										
S 19	S 20										
1985											
OPLS 644											
2665.87	<p>Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>T 4 S</td><td>R 35 E</td></tr> <tr><td colspan="2" style="text-align: center;">S 18</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td colspan="2" style="text-align: center;">S 19</td></tr> <tr><td colspan="2" style="text-align: center;">2005</td></tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>No accessories available.</p>	T 4 S	R 35 E	S 18		1/4		S 19		2005	
T 4 S	R 35 E										
S 18											
1/4											
S 19											
2005											

UNION COUNTY SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 209-2013R

T4S35N03

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 4 S., R. 35 E., Willamette Meridian, Oregon

FEET

The geographic position (NAD 1983 (CORS 96)) of this corner is:


Latitude: 45° 12' 40.937" N. Longitude: 118° 28' 32.363" W.

~~Continue over open level land.~~

4980.0 Dirt road, 14 ft. wide, bears N. 35° E. and S. 35° W.

5081.80 Point selected for the witness cor. for the cor. of secs. 13, 18, 19, and 24, hereinbefore described.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



from which

A fir, 24 ins. diam., bears S. 69¼° E., 19.4 ft. dist., mkd. X at breast height and BT at the base.

A spruce, 14 ins. diam., bears S. 7¼° W., 32.4 ft. dist., mkd. X at breast height and BT at the base.

A fir, 5 ins. diam., bears S. 60¼° W., 25.3 ft. dist., mkd. X at breast height and BT at the base.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

5131.80 True point for the cor. of secs. 13, 18, 19, and 24.

From the cor. of secs. 17, 18, 19, and 20.

N. 0° 7' 45" E., between secs. 17 and 18.

Over level land, through scattered timber.

2655.42 The ¼ sec. cor. of secs. 17 and 18, perpetuated in 1976 from original evidence no longer in existence, and in 1985, by Duane I. Griffith, Professional Land Surveyor No. 644, and recorded as Survey No. 43-76 at the Union County Surveyor's Office, in LaGrande, Oregon, subsequently utilized in 1989, by Leland Lee Myers, Professional Land Surveyor No. 699, recorded as Survey No. 21-89 at the Union County Surveyor's Office in LaGrande, Oregon, monumented with an aluminum post,

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 209-2015R