## Dependent Resurvey of a Portion of the West Boundary, T. 4 S., R. 35 E., Willamette Meridian, Oregon

FEET The geographic position (NAD 1983 (CORS 96)) of this corner is: Longitude: 118° 29' 06.926" W. Latitude: 45° 11' 49.057" N. N. 0° 06' 30" E., bet. secs. 19 and 24, on the W. bdy. of the Tp. Over rolling land, through scattered timber. Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate 2644.91 distance, there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T 4 S 1/4 4535 Pol R 34 E | R 35 E S 24 | S 19 2005 from which A pine, 18 ins. diam., bears S. 22° E., 40.1 ft. dist., mkd. 1/4 S19 BT. A pine, 10 ins. diam., bears S. 61½° W., 17.7 ft. dist., mkd. 1/4 S24 BT. Deposit a magnet in a white plastic case at the base of the stainless steel post. Corner is located 10 ft. E. of a barbed wire fence. The geographic position (NAD 1983 (CORS 96)) of this corner is: Latitude: 45° 12' 15.169" N. Longitude: 118° 29' 06.861" W. Continue over gently rolling land, through sparse timber and native grasses. Point for the cor. of secs. 13, 18, 19, and 24, at proportionate 5289.82 distance, there is no remaining evidence of the original cor. This point falls in middle of Corral Creek, 10 ft. wide, drains N. 10° E., impracticable to set a permanent monument. UNION COUNTY From this point, the point selected for a witness cor. bears SURVEYOR S. 89° 11' 50" E., 50.00 ft. dist., hereinafter described.

Date Received 3/8//3 N. 0° 06' 03" E., bet. secs. 13 and 18, on the W. bdy. of the Tp.

Date Filed 3/8//3

By 2/2-20/3/2

File No. 2/2-20/3/2