
History of original corner establishment: Corner established by Rufus S. Moore under General Land office contract no. 451, dated June 12, 1882. Surveyor General Records states:

Set a basalt stone 20''x14''x12'', 15 minches in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on W face from which:

A Fir 9" in diameter bears \$27°E, 60 lks. dist. marked \s BT

A Fir 14" in diameter bears \$26 $^{\rm o}$ W, 67 1ks. dist. marked $\frac{1}{4}$ \$ 3T



No record of subsequent remonumentation was found in County Records.

Description of corner evidence found:

A 15" Douglas Fir \$27°E, 39.6 feet dead and down with scribes visible.

A 17" White Fir S 26° W, 44.2 feet alive, sickly with scribes visible.

See map of survey dated November 1985.

Description of monument and accessories I established to perpetuate the

set a 2½ x30" aluminum pipe with aluminum cap marked as shown, 30" in the ground with surrounding mound of stone, from which:

A 13" Douglas Fir bears $$80^{\circ}E$, 11.36 feet, marked $\frac{1}{4}$ \$23 BT

A 15" Ponderosa Pine bears N35°W, 5.00 feet marked $\frac{1}{4}$ \$22 BT

Set steel fence post approximately 5 feet East with 54-4 and 54-2 signs attached.

Set steel fence post approximately 5 feet South with 54-2 sign attached.

Corner set 9/30/85 Witness: None

OREGON
JULY 10, 1964

DUANE I. GRIFFITH
644

REGISTERED PROPESSIONAL LAND SURVEYOR

Brass washer nailed to BT blaze.
Used steel tape and magnetic compass with 20° East declination. Measured to 50d spike set in right side of tree when facing tree, unless otherwise stated.

Office of	of	
State of, I hereby certify that the will	thin instrument was 611 to	· · · · · · · · · · · · · · · · · · ·
for record on the day of 1	<i>'9</i> .	
COUNTY OFFICIAL NION COUNTY	Ţ	
SURVEYOR	(DEPUTY)	

Form R6-7100-57 (9/71)

Date Received 12-5-85

Date Received 15 3 03

Date Filed 12-6-85

BY G. LANGLITZ DEPUTY

File No. 154-85 R

☆U.S. GOVERNMENT PRINTING OFFICE-1983-793-276

P 17