History of original corner establishment: Corner established by Rufus S. Moore under General Land office contract no. 451, dated June 12, 1882. Surveyor General Records states: Set a basalt stone 14"x10"x7", 10 inches in the ground for corner to sections 28, 29, 32, & 33 marked with 1 notch on S and 4 notches on E edges and raised a mound of stone alongside from which:

DIAGRAM T43 R 35 E 29

A Pine 12" in diameter bears \$37°W, 229 lks. distant, marked T4S R35E S 32 BT

No record of subsequent remonumentation was found in County Records. Description of corner evidence found:

Found stone 14"x10"x7" with notches visible in edge of mound of stone.

Found 20" Ponderosa Pine alive and vigerous, \$370 W, 229 1ks. scribes visible.

See map of survey dated November 1985.

Description of monument and accessories I established to perpetuate the

original location of this corner: In place of the stone, I set a 2½x30" aluminum pipe with aluminum cap marked as shown, 28" in the ground with surrounding mound of stone, from which:

A 5/8"x30" iron pin with plastic cap marked BGA Survey Marker Bears N70°E, 6.36 feet.

A 16" Ponderosa Pine bears \$44°E, 55.53 feet, marked T4s R35E s 33 BT.

A 6" Ponderosa Pine bears N49°W, 11.66 feet, marked X BT.

Buried original stone west.

REGISTERED

Set steel fence post approximately 5 feet North, with 54-4

sign attached. Corner set 10/23/85

Witness: Greg Blackman, Rick Robinson

GRIFFITH T4S R35E S 29 s 28 S 32 s 33 1985 64

PROFESSIONAL AND SURVEYOR OREGON DUANE I. GRIFFITH

Brass washer nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Measured to 50d spike set in right side of tree when facing tree, unless otherwise stated.

Office of		
State of , I hereby certify that the within instrument was filed in this office		
for record on the day of, 19		
(COUNTY (FFICIUNION COUNTY SURVEYOR	(DEPUTY)

Form R6-7100-57 (9/71)

Date Received 12-5-85

Date Filed 12-6-85

File No. 174-85R

\$U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276

V 9