
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Herman D. Gradon under GLO contract number 452, dated June 16, 1873. Surveyor General record states:

Set a basalt stone 14x8x5 ins 9 ins in the ground for $\frac{1}{4}$ sec cormarked $\frac{1}{4}$ on W face, from which:

A Pine 10 ins diam bears N5°E 56 lks dist marked ¼ S BT A Pine 6 ins diam bears S65°W 90 lks dist marked ¼ S BT



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found a stone 15x8x5 inches marked $\frac{1}{4}$ on W face, sitting erect in a mound of stone.

Found a 20 inch diameter Ponderosa Pine S65°W, 58.90 feet (to a 50d spike driven in the right side of the root crown) live and vigorous with blaze evident. (I did not open.)

Found no evidence of the Northeast bearing tree.

Description of monument and accessories I established to perpetuate the

original location of this corner: In place of the found original corner stone, I set a $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown, 26 inches in the ground, from which:

New BT:

A 8 inch diameter Ponderosa Pine bears N40°E, 29.08 feet marked ¼ S1 BT

Raised a mound of stone around monument, 3 ft. base to top of cap.


Painted a 6 inch red band around all BTs and attached bearing tree and land survey monument signs.

Set a steel fencepost approximately 5 feet South with land survey monument sign attached.

Buried the original corner stone Northwesterly and alongside of monument.

I hereby certify that the above corner point was perpetuated as hereon described on November 12, 1987.

Witnesses: Rick Robinson and Jeff Petersen



PROFESSIONAL LAND SURVEYOR

OREGON
JULY 10, 1964

DUANE I. GRIFFITH

REGISTERED

I used a steel tape and magnetic compass in the establishment of new accessories. I used 19° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of	County of
	ify that the within instrument was filed in this office
for record on the day of	, 19
	. by
(COUNTY OFFICIAL)	(DEPUTY)

Form R6-7100-57 (9/71)

1-9

C-21 8, G, LANGLITZ DEANY
File No. 164-87 R

UNION COUNTY SURVEYOR 2-0