CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:


Record of the original survey by Herman D. Gradon, Contract No. 452, 1882, <u>states:</u>

Set a basalt stone, 14x9x5 ins., 8 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face,

From which:

A Pine, 12 ins. diam. bears $N5^{0}E$, 45 lks. dist. marked 1/4 S BT.

A Pine, 20 ins. diam. bears $S45^{O}W$, 9 lks. dist., marked 1/4 S BT.



Description of corner evidence found:

Found: The original corner stone, 14"x9"x5" lying loose with plain chisel markings "1/4" visible on the top surface.

We establish the $\underline{\text{True}}$ $\underline{\text{Corner}}$ $\underline{\text{Point}}$ from the remains of the original bearing trees as follows:

An orig. 12" Pine, now an approx. 16" rotted stump, uprooted during recent logging, no marks remaining, the stump hole of which bears $N7^{0}E$ 29.7 ft.

And an orig. 20" Pine, now a 22" Ponderosa Pine snag, with scribing "1/4 S BT" visible on an unhealed double blaze, bears $S35^{O}W$ 5.9 ft.

Description of monument and accessories I established to perpetuate the

original location of this corner: At the <u>True Corner Point</u>, we set a 2"x30" Galvanized Iron Pipe, 22" in the ground, with original stone buried upside down along west side of pipe, with brass cap attached, marked:

From which new bearing trees:

A 6" Douglas Fir, scribed "1/4 S 18 BT" on a double blaze bears N $4\frac{1}{2}{}^{0}$ W 12.1 ft.

And a 12" Douglas Fir, scribed "1/4 S17 BT" on a double blaze bears $582^{\circ}E$ 12.4 ft.

Attached brass washer, stamped "LS 1099" to lower blaze of new BTs.

Placed steel fence post 5 ft. N of monument with sign 54-4 attached.

Attached signs and painted all BTs except orig. NE stump per <u>Standard Specifications for Cadastral Survey</u>, U.S.F.S., Region 6, Oct., 1979

Compass Declination: 200 East.

1/4 S18 + S17 PLS 1099 1980

REGISTERED

T4S R36E

I hereby certify that the above described corner and/or accessories was established on September 9, 1980.

Witness: John Curtiss

File No. 475 - 84 R

		PROFESSIONAL LAND SURVEYOR
Office of County Surveyor County of	, Union	Lary Lofanglit
State ofOregon I hereby certify that the within instrument was filed in this office		
for record on the day of by	SIDNEYOR	GARY L. LANGLITZ 1099
(COUNTY OFFICIAL)	(DEPUTY)	
Form R6-7100-57 (9/71)	Outo Received	☆ GPO798-276
	Date Filed	