

Index File No. L-17

CORNER RECORD (SEARCH)
(Ref. FSM 7151.4)

Tract or Survey No. _____ Cor. No. _____


T. 75 R. 36E

R.D. LAGRANDE County UNION

Merid. Will

N.F. W-W State OR

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

BASALT STONE 16x7x7 IN MOUND OF STONE MARKED WITH POOR 1/4. STONE IS VERY SOFT.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

PHOTO IDENTIFICATION DATA

Photo No. 477-195
Filed At. LAGRANDE
Object Ident. APPROX 1/4 CORN.
Ident. By DAVE DAHLSTROM
Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

FROM FENCE CORNER AT SE COR TO SEC. 15 FOLLOW FENCE NORTH TO WHERE FENCE TURNS WEST, GO EAST ABOUT 300' MOUND IN SMALL OPENING.

PLANE COORDINATE POSITION DATA

State _____ Zone _____
X _____
Y _____
Estab. By _____ Agency _____

Signature

Title

DAVE DAHLSTROM TIM LUSHER

Division

Headquarters

6-17-86 Date

FS-7100-52 (3/68)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	<u>12-21-87</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>306-87R</u>

L-17

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


T 4S, R 36E., W.M.

Corner Code No. L-17

Note: Monument marked as shown below

History of original corner establishment:

This corner was originally established by Herman D. Gradon, U.S. Deputy Surveyor, under Contract No. 452, dated June 16, 1882. The original notes state that at the corner a 17 by 8 by 7 inch basalt stone, marked 1/4 on west face, was set 11 inches in the ground with a mound of stone raised alongside.



Corner No.
Compass Declination: 19.0°E

Description of corner evidence found:

Found 12 by 8 by 7" basalt stone, loose in the center of a mound of stone, with a faint "1/4" marked on it. The markings have been virtually destroyed by a previous searcher using a wire brush.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the found original stone, set a 2 1/2" by 30" aluminum pipe with 2 1/2" aluminum cap, 15" in the ground to bedrock and surrounded with a mound of earth and stone from which:

A 13" ponderosa pine bears S55 1/2°E 38.1' scribed 1/4 S14 BT.

A 10" ponderosa pine bears N15°W 41.4' scribed 1/4 S15 BT.

New bearing trees have a brass washer stamped PLS 1106 nailed to the face of blaze. Attached sign 54-3 and 54-9 and painted face of blaze and a 6" red band around each bearing tree. Set steel fence post North of corner and attached sign 54-9.

UNION COUNTY SURVEYOR
Date Received <u>1-5-89</u>
Date Filed <u>1-6-89</u>
By <u>G. LANGLITZ DEPUTY</u>
File No. <u>1-89 R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL)

.....
(DEPUTY)

L-17