

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Index File No N-3

**History of original corner establishment:**

Record of the original survey by Herman A. Gradon, Contract No. 452, dated 1882 states:

Set a basalt stone, 18x10x6 ins., 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on N face, from which:

- a Fir, 10 ins. diam. bears North 15 lks. dist., marked 1/4S BT
- a Fir, 8 ins. diam. bears S40°W 23 lks. dist., marked 1/4 S BT



**Description of corner evidence found:**

Found: A stone, 10"x6" exposed 6", leaning westerly, with plainly visible "1/4" chiseled on North face, (stone found to measure 18"x10"x6" when later removed)

From which: The remains of the original bearing trees:

- A 10" Douglas Fir stump, 3 ft tall, rotten, with scribing "BT" visible on an unhealed blaze bears North 9.9 ft. from the base of the corner stone,
- A 10" Douglas Fir stump, 1 ft. high, partially rotten, (the tree portion is located approx. 5 ft. East of the stump, with well-healed double blaze visible) bears S40°W 15.2 ft., from the base of the corner stone.

**Description of monument and accessories I established to perpetuate the original location of this corner**

At the base of the corner stone, we set a 2"x30" Iron Pipe, 20 ins. in the ground with the original corner stone buried upside down along the West side of this pipe, with brass cap attached marked:

T4S R36E  
S18 — 1/4  
S19  
PLS 1099  
1980

From which we mark new BT's

- An 8" Douglas Fir, scribed "1/4 S19 BT" on a double blaze bears S60°W 14.3 ft.,
- A 10" Douglas Fir, scribed "1/4 S18 BT" on a double blaze bears N26°W 32.8 ft.

Attached brass washer, stamped "LS 1099" to lower blaze of new BT's.  
Placed steel fencepost w/sign 54.4 attached 5 ft. West of corner.

Attached signs and painted BT's per Standard Specifications For Cadastral Survey, U.S.F.S. Region 6, Oct. 1979  
Compass Decl. 20°E.

Witness: Mike Wagoner  
I hereby certify that the above described corner and/or accessories was established on Aug. 20, 1980.

Office of County Surveyor County of Union  
State of Oregon, I hereby certify that the within Instrument was filed in this office for record on the \_\_\_\_\_ day of \_\_\_\_\_  
\_\_\_\_\_  
(COUNTY OFFICIAL) by \_\_\_\_\_ (DEPUTY)



**UNION COUNTY  
SURVEYOR**

By Received \_\_\_\_\_

REGD 796 304

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 480-84R