

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. N-5

History of original corner establishment: Record of the original survey by Herman D. Gradon, Contract No. 452, dated 1882.

States:


Set a basalt stone, 14x12x8 ins., 9 ins. in the ground for cor. to secs. 17, 18, 19, and 20, marked with 3 notches on S and 5 notches on E edges, from which:

A Mahogany 7 ins. diam. bears N80°E 79 lks. dist., marked T4S R36E S17 BT.

A Pine 6 ins. diam. bears S55°E 59 lks. dist., marked T4S R36E S20 BT.

A Pine 8 ins. diam. bears N20°W 163 lks. dist. marked T4S R36E S18 BT.

No other trees within limits, raise mound of stone alongside.



Description of corner evidence found:

Found: No trace remains of the corner stone or mound of stone.

We establish the True Corner Point at record distance from the orig. NE BT and at average distances from the original NW and SE BTs as follows:

An orig. 7" now 8" Mahogany, alive, with faint scribing "T" visible, on an unhealed blaze bears N75°E 52.1 ft.

An orig. 6" now 28" Ponderosa Pine, alive and well healed bears S42½°E 40.5 ft.

And an orig. 8" now 24" Ponderosa Pine, alive and well healed bears N24°W 109.2 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the True Corner Point, we set a 2"x30" Galvanized Iron Pipe, 16 ins. in the ground on a rocky SW slope, raise mound of stone 4' diam. and 1 ft. high around pipe, with brass cap attached.

Marked:

From which we mark a new BT.

A 20" Ponderosa Pine, scribed "T4S R36E S20 BT" on a double blaze bears S13°E 86.5 ft.

Attach brass washer, marked "LS 1099" to lower blaze of new BT.

Placed steel fence post 5 ft. N and 5 ft. E of corner with signs 54-2 and 54-4 attached to northerly post, sign 54-2 to easterly post.

Attached signs and painted all BTs per Standard Specifications for Cadastral Survey, U.S.F.S. Region 6, October, 1979.

Compass Declination: 20°E.

T4S R36E  
S18 | S17  
S19 | S20  
PLS 1099  
1980

I hereby certify that the above described corner and/or accessories was established on August 21, 1980.

Witness: Mike Wagoner

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**  
*Gary L. Langlitz*  
**OREGON**  
JULY 22, 1977  
**GARY L. LANGLITZ**  
1099

Office of..... County Surveyor..... County of..... Union.....  
State of..... Oregon..... I hereby certify that the within instrument was filed in this office  
for record on the..... day of..... 19.....  
..... by  
(COUNTY OFFICIAL)

**UNION COUNTY  
SURVEYOR**

---

Received \_\_\_\_\_

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 481-84 R