## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishments

Original survey by General Land Office (contract survey 1882)
The original notes state; Set a bakalt stone 12x10x5 ins.
from which; A pine 22" in diam bears N30°W 53 lks dist
marked ‡SBT.;
A pine 15" in diam bears S15°W 39 lks dist marked ‡SBT;

|                     | N-23   |
|---------------------|--------|
| DIAGRAM             |        |
| T4S                 | R36EWM |
| <u>\$13</u><br>\$24 |        |

## Description of serner evidence found:

Found stone marked 1

Found - A pine at N30W ( now a stump with BTscribe;

Found - A pine snag bears S15.W 39 lks with \$5 BT scribe.;

REGISTERED
OREGON
LAND SURVEYOR

MAY 4, 1956
JAMES G. VOELZ
381

## Description of monument and accessories I established to perpetuate the original location of this corner

At the postion of the corner I set a 2" galvanized pipe 30" long and with a 8" plate welded to bottom. The pipe set to a depth of 19" and back filled with stone and soil and raised a stone monument. I placed the marked stone on top of monument. A bronze cap was placed on top of pipe.

I stamped the disk

†COR T4S R36E S13

File No. 493-84 R

At the position of the corner the original bearing trees are;

Original trees are unsatisfactory condition; I set the

following new bearing trees; A fir 12" in diam bears N37°W 25.9

ORE LIC 381

ft. dist marked \$SBT; A pine 30" in diam bears S70°W 54.5 ft. dist

1969

I set a steel fence post with USFS sign 54-4 attached. I placed

a USFS National Forest Boundary sign on the post indicating National Forest land to South. I placed USFS bearing tree sign on both old and new bearing trees shoulder high facing the corner.

| Office of                                       | 1                           |
|---|-----------------------------|
| for record on the 9 day of Sapt 1969 9 oclock P | .m., (signed) Date Received |
|   | Date Filed                  |
|   | Ву                          |