CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Record of the original survey by Jacob Cooper, Contract No. 397, dated 1881, states:

Set post 4 ft. long, 4 ins. square, 2 ft. in ground on E. hillside in prairie for cor. to secs. 19, 24, 25 and 30, marked T4S S19 on NE, R36E S30 on SE, R35E, S25 on SW, and S24 on NW faces, with 2 notches on S and 4 notches on N edges, from which:

A Pine 32 ins. diam. bears S55⁰E 146 lks. dist., marked T4S R36E S30 BT.

Record of the subdivisional survey of T4S R36E by H. Gradon, 1882 states:

I raised a mound of stone around post.

Index File No. R-1 DIAGRAM **T4S** 24 | 19 R R 35 36 25 T 30 Ε Ε

Description of corner evidence found:

Found: Remains of the Gradon stone mound, no trace of the original post, from which: The only original bearing tree, an original 32" Pine, now a 32" Ponderosa Pine, alive and in good condition, with faint scribing "R36 S30" visible on an unhealed blaze bears S52°E 96.4 ft.

Description of monument and accessories I established to perpetuate the

original location of this corner: At the <u>True Corner Point</u> in the 1882 mound of stone, we set a 2"x30" <u>Galvanized Iron Pipe</u>, 18" in the ground to bedrock, and supported in a mound of stone, 3 ft. diam. 1 ft. high, with brass cap attached, marked:

From which we mark new BTs:

A 26" Ponderosa Pine, scribed "T4S R36E S19 BT" on a double blaze bears N53°E 206.6 ft.

And a 14" Ponderosa Pine, scribed "T4S R36E S30 BT" on a double blaze bears S84ºE 115.2 ft. Attached brass washer, stamped "LS 1099" to lower blaze of new BTs.

Placed steel fence post 5 ft. North of monument with sign 54-4 attached.

Attached signs and painted BTs per Standard Specifications for Cadastral Survey, U.S.F.S. Region 6, October, 1979. Compass Declination: 20°East.

> I hereby certify that the above described corner and/or accessories was established on September 9, 1980.

Witness: John Curtiss

LAND SURVEYOR ary & gang OREGON JULY 22, 1977 GARY L. LANGLITZ 1099

REGISTERED PROFESSIONAL

T4S

S19

S30

36

Ε

S24

S25 |

PLS 1099 1980

R

35

Office of County Surveyor County of Union State of.....Oregon ... , I hereby certify that the within instrument was filed in this office for record on the...... day of......, 19.....

.....by (COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

.....UNION COUNTY SURVEYOR Date Received Date Filed_ File No. 495-84 R