
# ATIFIED RECORD OF LAND CORNER MONUMENT

#### HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by Herman D. Gradon under GLO contract Number 452, dated June 6, 1882. Surveyor General record states:

Set basalt stone 14x8x8", 9 ins. In the ground for 1/4 sec cor. marked 1/4 on N. face from which:
A pine 36 ins diam bears S 25° W 240 lks dist marked 1/4

SBT. No other tree within limits and raised a mound of stone alongside.



### DESCRIPTION OF CORNER EVIDENCE FOUND:

None

See Union County Survey Number 011-2009

## DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

## TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a 2 ½" x 30" Aluminum pipe, with aluminum cap marked as shown, 10" in the ground, with 3 ft. wide mound of stone, from which:

- A 5/8" x30" iron pin with 1  $\frac{1}{2}$ " Aluminum cap bears North 45°16' East, a distance of 14.18 feet, marked NE RP.

- A 17" Ponderosa Pine bears South 62° East, a distance of 89.25 feet, marked 1/4 S9 BT. A 24" Ponderosa Pine bears South 11° West, a distance of 78.85 feet, marked 1/4 S9 BT. A 5/8" x 30" iron pin with 1 ½" Aluminum cap bears North 37°28' West, a distance of 21.53 feet, marked NW RP

Set a steel fencepost 2 feet North of corner.

I hereby certify that the corner was perpetuated on May 22, 2009 Witness: Jeff Hsu, Gregory T. Blackman, Jr.

REGISTERED **PROFESSIONAL** .AND SUK∜VE∳YOR


OREGON

RICK G. ROBINSON

2219

Renewal Date: December 31, 2010

UNION COUNTY **SURVEYOR** Date Received File Number \_\_\_



I used a steel tape and magnetic compass in the establishment of the bearing trees. I used 18° East I attached a brass washer marked OPLS declination. 2219 to the BT blaze. The distance is to a 60d spike driven into the root crown at the right side of the new bearing tree. I used a Leica 1200 GPS in the establishment of the iron pin accessories. bearing is as per Survey Number 011-2009.