
## UNION COUNTY SURVEYOR CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None, corner not originall set.

Description of corner evidence found:



See Union County Survey Map 026-1996

Description of monument and accessories I established to perpetuate the original location of this corner:

At position determined from survey I set a 2½" x 30" aluminum pipe monument with a  $2\frac{1}{2}$ " aluminum cap stamped as shown below, 26" in the ground, from which:

A 19" Ponderosa Pine bears N6°E, 109.05 feet, marked CW 1/16 S15 BT. A 15" White Fir bears S71°E, 57.15 feet, marked CW 1/16 S15 BT. NEW BEARING OBJECTS:

I hereby certify that the corner was monumented on June 26, 1996. Witness: Mark Durbin, Jeff Madsen

REGISTERED **PROFESSIONAL** LAND SURVEYOR

you tolan OREGON

**GREGORY T. BLACKMAN** 991

Ronanal Date: December, 31 1997

<i></i>	GRIFF	ITH & S	
4 8 8 4 5 4 5 4 5 5 5 5 5 5 5 5 5 5 5 5	T 4 S	R 37 E	7( 7 C + 3 P Z
W 1/16			
C		C 15	
1996			
	OPLS	991	

UNION COUNTY **SURVEYOR** Date Received 7-3-96

Date Filed 7-3-96

Filed By J. Peterson, Deputy

File Number 062-1996 R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 17° East declination. The distances are to a 60d spike driven into the right side of the root crown of the bearing trees.